



## Tank Dryer

Absorption Water | Adsorption Material and Desiccant



The GIEBEL Tank Dryer absorbs harmful water from diesel, biodiesel, gas oil and fuel from the bottom of your drums. Removing water from your fuel or hydraulic oil reduces your maintenance costs and downtime.

The Tank Dryer is a tank sock filled with superabsorbent. Superabsorbents can absorb many times their own weight of a given liquid. The superabsorbent we use is highly hydrophilic and can therefore absorb a lot of water. Simply pass the Tank Dryer through the opening of a tank. The Tank Dryer will then sink to the bottom and absorb the water from the tank.

After 60 minutes to a maximum of 72 hours, you can pull the Tank Dryer out of the tank by the cord and have successfully removed water.



Transformers



Hydraulic Power Packs



Gears



Storage Tanks



Barrels & IBC

|                       |   |
|-----------------------|---|
| <b>Use</b>            | Removal of harmful water from tanks                                 |
| <b>Operating Time</b> | After 60 minutes the effect is finished. Maximum duration 72 hours. |
| <b>Usable for</b>     | Gasoline, Kerosene, Diesel, Mineral oil, Long-chain hydrocarbons    |
| <b>Not usable for</b> | Alcohols, Urea  |
| <b>Capacity</b>       | Absorbs up to 1 liter of water per sock.                            |
| <b>Size</b>           | 600 x 60 x 10 mm  |
| <b>Size of Cord</b>   | 5 m   |
| <b>Weight</b>         | 100 g   |
| <b>Regenerable</b>    | No  |

Online for Download:



**Silica Gel,  
Molecular Sieve  
& Adsorber**  
[shop.giebel-adsorber.de](http://shop.giebel-adsorber.de)  
Order in our Online Shop  
24/7

We would be pleased to advise you personally  
**+ 49 79 46 94 44 01-0 | [info@giebel-adsorber.de](mailto:info@giebel-adsorber.de) | [giebel-adsorber.de](http://giebel-adsorber.de)**